

TECHNICAL DATASHEET

Mayline 35L

Elastic self-sealing liquid

Elastic self-sealing liquid for heating installations with daily leakage of up to 35 litres

Mayline 35L seals leaks of up to 35 litres per day. The self-sealing liquid is based on the principle of providing a mechanical seal from the outside. Mayline 35L only functions in the presence of oxygen and is suitable for all materials currently in use (synthetic and metallic). The product provides the seal with a certain elasticity. The product can even be used in open expansion tank systems.



Mayline 35L
Liquido autosigillante elastico
 Liquido autosigillante elastico per impianti di riscaldamento con perdita giornaliera fino a 35 litri

ATTENZIONE
 Contiene Sodio Solfato.
 Indicazioni di pericolo: H229 Provoca grave irritazione cutanea. H332 Provoca irritazione cutanea. H335 Può irritare le vie respiratorie.

Consigli di prudenza
 P211 Evitare di respirare la nebulosa e i vapori.
 P260 Evitare di inalare la nebulosa e i vapori.
 P273 Evitare di scaricare in acqua.
 P280 Indossare guanti protettivi e proteggere il viso.
 P303 In caso di contatto con gli occhi lavare con acqua e consultare un medico.
 P305+P351+P338 In caso di contatto con gli occhi lavare bene con acqua e consultare un medico. In caso di contatto con la pelle lavare bene con acqua. Portare guanti e occhiali di protezione. Rimuovere immediatamente con acqua. In seguito: come guanti, occhiali, lavanda, ecc.

Consigli di prudenza
 P211 Evitare di respirare la nebulosa e i vapori.
 P260 Evitare di inalare la nebulosa e i vapori.
 P273 Evitare di scaricare in acqua.
 P280 Indossare guanti protettivi e proteggere il viso.
 P303 In caso di contatto con gli occhi lavare con acqua e consultare un medico.
 P305+P351+P338 In caso di contatto con gli occhi lavare bene con acqua e consultare un medico. In caso di contatto con la pelle lavare bene con acqua. Portare guanti e occhiali di protezione. Rimuovere immediatamente con acqua. In seguito: come guanti, occhiali, lavanda, ecc.

Info: 0300-F091-3009-ANDP

Maychem s.p.a.
 Via Nappioli, 15
 39100 Bolzano (BZ)
 Tel.: 0471/052852 - Fax: 0471/1968339
 P.IVA: 11064850217
 info@maychem.it - www.maychem.it

Anno di produzione: 2021

5 l
 5 l

code	package
5/MY35L	5 l canister
1/MY35L	1 l (pack of 12 bottles)
2/MY35L	1 l (pack of 2 bottles)



Instructions for use

Quantify the daily leakage. Quantify the system's contents. Bleed the pumps well after inserting the liquid! Remove or bypass all the filters and screens. Adjust the boiler's maximum temperature and pressure. Open all radiator valves and mixing valves completely. Bleed the re-circulation pumps well and leave them in function. Use a loading pump to insert the necessary amount of self-sealing liquid. Bleed the re-circulation pumps again. The system must remain in function for at least 7 hours at maximum temperature. The Mayline35L may be left inside the system, but if a protective agent with inhibitors is used, than the self sealing liquid solution must be removed. If necessary, drain the system's water to eliminate any eventual residues.

Important note


Shake the container well before use. Mayline 35L can be mixed with glycols and antifreezes but NOT with other chemical products. The self-sealing liquid may be left inside the system, but if a protective agent with inhibitors is used, than the self sealing liquid solution must be removed.

Protect the product from frost.

Mixing proportions

1-2% (1-2 litres of Mayline 35L for every 100 litres of water).
 ATTENTION! THE PRODUCT MUST NOT BE OVER OR UNDER DOSED.

Application time 7 hours with high temperature of at least 5 degrees Celsius and high pressure of at least 0.7 bar compared to the normal operating pressure.



Security instructions

In the event of eye contact, rinse eyes thoroughly with much water and consult a doctor. In the event of skin contact, rinse well with water. Wear gloves and protective eyewear. Use water to immediately remove the product from objects such as tiles, flooring, wash basins, etc. Keep out of reach of children!

Disposal

For information concerning the disposal of effluent and liquid waste, please consult the corresponding safety data sheet.

Mayline 35L

Elastic self-sealing liquid



Elastic self-sealing liquid
for heating installations

WARNING

Contains: Silicic acid, sodium salt

Hazard statements:

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

Precautionary statements:

P261 Avoid breathing mist and vapours.

P280 Wear protective gloves and face protection.

P264 Wash the hands thoroughly after handling.

P312 Call a POISON CENTRE or a doctor if you feel unwell.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Notes
